

New
TSC 513



**START YOUR NEW JOURNEY
WITH A LOT OF BENEFITS**

**Easy & Smart Gear Shift,
More Operator Comfort!**



**...The Next Generation
Combine Technology**



Full Straw



**Free
Tool Kit**



**No Grain
Breakage**



**Low
Maintenance**



**No Grain
Loss**

STANDARD TSC-513



Technical Specifications

| HARVESTER SIZE | 51"-13' | | 54"-14' | |
|--------------------------|--------------------------|-----------|--------------------------|--------------|
| Reel Assembly | | | | |
| Type | Tyne Pick up Reel | | Tyne Pick up Reel | |
| Dia(mm) | 925 | | 925 | |
| Width(mm) | 3815 | | 3830 | |
| Cutter Bar | | | | |
| Width(mm) | 4045 | | 4270 | |
| Height(mm) | 35-1140 | | 35-1140 | |
| Threshing Drum | Wheat | Paddy | Wheat | Paddy |
| Type | Rasp Bar | Peg Tooth | Rasp Bar | Peg Tooth |
| Width(mm) | 1280 | 1270 | 1350 | 1342 |
| Cocave | Wheat | Paddy | Wheat | Paddy |
| Width(mm) | 1280 | 1280 | 1285 | 1285 |
| Strawwalker | | | | |
| Nos. | 5 (Five) | | 6 (Six) | |
| Length(mm) | 3610 | | 3610 | |
| Width(mm) | 240 | | 215 | |
| Cleaning | | | | |
| Type | Open Lip Frog Mouth Type | | Open Lip Frog Mouth Type | |
| Sieve | Front | Rear | Front | Rear |
| Length(mm) | 1522 | 635 | 1400 | 635 |
| Width(mm) | 1210 | 1210 | 1290 | 1290 |
| Blower | | | | |
| No. Blower Blade | Four(4) | | Four(4) | |
| Dia(mm) | 460 | | 540 | |
| Width(mm) | 1170 | | 1245 | |
| Capacity | | | | |
| Gear Box Oil (Ltr.) | 4 Ltr. | | 4 Ltr. | |
| Grain Tank(cu./m) | 1.7 | | 2 | |
| Overall Dimension | Working Position | | Working Position | |
| Length(mm) | 8510 | | 8510 | |
| Width(mm) | 4310 | | 4410 | |
| Height(mm) | 3750 | | 3750 | |

Features :

Good Custom Hiring Rates.

Higher Recovery From Crop.

No Grain Loss In Field.

Straw Can Be Used For Cattle Feed.

Less Maintenance, Easy Dismantling & Re-fitting.

STANDARD CORPORATION INDIA LIMITED

Standard Chowk, Barnala - 148101, Punjab, India | Helpline : 97800-24233, 25233
www.standardcorp.in | Mail : combines@standard.in | info@standardcorp.in

